Large Capacity Open Fryers

OFG 341 1-well gas OFG 342 2-well gas



OFG 342 2-well large capacity gas open fryer with Computron™ 8000 control

Henny Penny open fryers offer high-volume frying with programmable operation, oil management functions and fast, easy filtration.

The 340 series large capacity open fryers offer maximum frying surface area within an economical footprint. A larger, shallower fry vat produces more consistent frying results with items that float when cooking.

Henny Penny gas open fryers combine reliability and efficient heating to recover temperature very quickly. Fast recovery translates into higher throughput, lower energy costs and longer frying oil life.

Henny Penny open fryers have a built-in filtration system that filters and returns hot frying oil in minutes. No separate pumps and pans, no handling hot oil. Frequent filtering extends frying oil life, improves product quality and reduces oil costs.

The Computron™ 8000 control features automatic, programmable operation, as well as energy-saving, filtration and cook management functions.

The Computron™ 1000 control offers programmability in a simple, easy to use digital control panel with LED display.

Standard Features

- Heavy-duty stainless steel vats with 7-year warranty
- Larger, shallow vat offers large surface area that promotes more even cooking
- Specially designed "beach" accommodates oil displacement when lowering basket
- High-efficency burners with solid state ignition
- High reliability heat-exchange design for energy efficiency and fast recovery
- Cold zone below burners helps extend oil life
- High-limit temperature protection
- Built-in filtration with over-the-top oil return to flush remnants
- · Easy basket set and release
- Stainless steel construction for easy-cleaning and long life
- 4 heavy-duty casters, 2 locking

- Computron[™] 8000 control (additional charge)
 - 12 programmable cook cycles
 - Melt mode
 - Idle mode
 - Clean-out mode
 - Load compensation
 - Proportional control
 - Optional filter prompt and customizable filter tracking
 - 16-character digital display with multiple language settings
- Computron[™] 1000 control
 - Programmable
 - LED Time/Temp display
 - Simple UP/DOWN arrows

Accessories shipped with unit

- Fry baskets—please select one
 - ☐ 1 full basket per well
- □ 2 half baskets per well
- 1 basket support for each vat
- Lift tool for basket support
- Filter screen and filter envelope

Options available separately


- ☐ 3 third-size baskets per well
- ☐ Fryer Shortening Shuttle®
- Choose one:
- ☐ Filter rinse hose OR
- ☐ Direct Connect shortening disposal

☐ APPROVED	☐ APPROVED AS NOTED	☐ RESUBMIT
AUTHORIZED SIGNAT	DATE	



Large Capacity Open Fryers

OFG 341 1-well gas **OFG 342** 2-well gas



	OFG 341		OFG 342	
Dimensions Width Depth Height	23.25 in 41.00 in 50.00 in	(591 mm) (1042 mm) (1270 mm)	44.50 in 41.00 in 50.00 in	(1131 mm) (1042 mm) (1270 mm)
Crated Length Depth Height Volume Weight	46 in 30 in 66 in 53 ft ³ 391 lb	(1169 mm) (762 mm) (1676 mm) (1.5 m³) (178 kg)	51 in 46 in 66 in 90 ft ³ 650 lb	(1296 mm) (1169 mm) (1676 mm) (2.5 m³) (295 kg)
Heating natural gas or liquid petroleum 3 burners 120,000 BTU/hr 31.7 kW 0.50 in gas line		6 burners 240,000 63.4 kW 0.75 in ga	BTU/hr	

Bidding Specifications

Provide Henny Penny model OFG 341 or 342 large capacity gas open fryer, 90 lb or 43 L oil capacity per vat, with built-in filtration system.

Unit shall incorporate:

- Computron[™]1000 simple digital control OR
 Computron[™] 8000 control system (additional
 charge) with programmable or manual operation,
 LED digital display, idle and melt modes, load
 compensation, filtration tracking and 7-day history
- Fry vats of heavy duty stainless steel with 7-year warranty
- Shallow vat design with larger surface area and beach to compensate for load displacement
- 4 heavy-duty casters, 2 locking

90 lb or 43 L per vat

Oil capacity

Required clearances

Sides 4 in (102 mm) Back 4 in (102 mm)

Front 30 in (762 mm) remove filter pan

Electrical


Volts	Phase	Hertz	kW	Amps	Wire*	Cord & Plug Not available for all destinations
120	1	60	NI/A	12.0	2+G	Please contact
230	1	50	N/A	6.2	1NG	Henny Penny

Laboratory certifications









Continuing product improvement may subject specifications to change without notice.

24 Hour Technical Support: Henny Penny Technical Service 800 417.8405 technicalservices@hennypenny.com Henny Penny Corporation PO Box 60 Eaton OH 45320 USA

+1 937 456.8400 800 417.8417 +1 937 456.8434 Fax 800 417.8434 Fax www.hennypenny.com

